



Description

^{EN} Cylindrical wall surface mounted luminaire made of aluminium; surface light inset matt silver, white, black, copper or gold; surface housing powder coated in white, black or gold; passive cooling of LEDs with optimised heat sink geometry; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; binning initial ≤ 2 MacAdam; available in the light colours 2700 K, 3000 K and 4000 K; CRI ≥ 90 ; min. 80 % of the luminous flux after 50 000 hours; incl. high quality lens system; optionally symmetric direct or direct/indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; installation of variant DIRECT optionally for floor or ceiling illumination; degree of protection IP20; PC I; optionally non-dimmable or DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%)

^{DE} Zylindrische Wandanbauleuchte aus Aluminium; Oberfläche Lichteinsatz matt silber, weiß, schwarz, kupfer oder gold; Oberfläche Gehäuse weiß, schwarz oder gold pulverbeschichtet; passive Kühlung der LEDs durch optimierte Kühlkörpergeometrie; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe; Binning initial ≤ 2 MacAdam; lieferbar in den Lichtfarben 2700 K, 3000 K und 4000 K; CRI ≥ 90 ; min. 80 % des Lichtstromes nach 50 000 h Lebensdauer; inkl. hochwertiger Linsenoptik; wahlweise symmetrisch direkte oder direkt/indirekte Abstrahlcharakteristik; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige Lichtverteilung; Montage Variante DIRECT wahlweise zur Boden- oder Deckenaufhellung; Schutzart IP20; SK I; wahlweise nicht dimmbar oder DALI-2 Steuerung; flimmerfreier Sehkomfort durch analoge Stromstärkenregelung (Minimalwert 1%)


SASSO 60/100 round

wall

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 2-SDCM
L80 @ 50 000 h
SASSO 60 up to 2×747 lm
SASSO 100 up to 2×1250 lm
non DIM, DALI-2

Types



Housing colours



Inset colours



Light distributions



Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

HOUSING COLOUR

white	7
black	1
gold	9



INSET COLOUR

white	7
matt silver	4
black	1
gold	9
copper	6






BEAM ANGLE

opal lens


Options on request

COLOUR RENDERING INDEX

CRI ≥ 95 2-SDCM



SASSO 60 round wall



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11W	2700 K	667lm	0 4 8 - 3 1 5 0
	3000 K	704lm	
	4000 K	747lm	


luminous flux white material colour

DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2 × 11W	2700 K	2 × 667lm	0 4 8 - 3 1 6 0
	3000 K	2 × 704lm	
	4000 K	2 × 747lm	

luminous flux white material colour

SASSO 100 round wall



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
20W	2700 K	1140lm	0 4 8 - 3 4 5 0
	3000 K	1190lm	
	4000 K	1250lm	

luminous flux white material colour


DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
2 × 20W	2700 K	2 × 1140lm	0 4 8 - 3 4 6 0
	3000 K	2 × 1190lm	
	4000 K	2 × 1250lm	

luminous flux white material colour


LIGHT DISTRIBUTION

opal lens



direct

opal lens



direct/indirect

Optical accessories

HONEYCOMB LOUVER

TYPE	ORDER CODE
SASSO 100 round	0 0 7 - 1 9 6 5 1 9 8